

SERIES 2

THE VALUE PACKED PROVEN PERFORMER

The Ero® garage door opener offers great value for money. With important features included, Ero®'s 650N motor will drive most standard residential sectional doors.

It's the choice for new homebuyers and for all the right reasons. It comes standard with the important features of TrioCodeTM128, Intelligent Safety System, Door Profiling and Soft Start/Soft Stop. It also includes a Standard Courtesy Light, and conveniently a service indicator to remind you when your door needs servicing.

WHAT'S IN THE BOX:







Three TrioCode[™]128 Remote Controls

[^]When maximum spring balanced weight is 20kg.

*Please see full warranty terms and conditions on our website. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under the Australian Consumer Law.

AT A GLANCE:



SECURE & RELIABLE REMOTE CONTROL

The TrioCode™128 remote control ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol (with trillions upon trillions of random codes*) for the ultimate in security.

*340,282,366,920,938,463,463,374,607,431,768,211,456 codes

POWERFUL MOTOR

This DC motor generates a peak pulling force of 650N and reliably lifts garage doors up to 100kg of weight.

COURTESY LIGHT

A built-in Courtesy Light means your immediate surrounds can be lit to provide security and convenience

5 YEAR WARRANTY

The Series 2 Ero® is backed by a 5 year/ 10,000 cycle warranty*, giving you peace of mind.

www.automatictechnology.com.au ♀ Phone: 1300 133 94



ERO GD0-11 TECHNICAL SPECIFICATIONS

Power	Input Voltage	230-240V a.c. 50Hz
	Transformer Rating	72VA
	Standby Power	2.2W
	Motor Type	24V d.c. Permanent Magnet
	Motor Power	100W
	Short-term Lifting Force	650N
Door Sizes	Maximum Door Weight [^]	100kg
	Rated Door Area	13.5m²
	Typical Travel Speed (door dependent)	140mm/sec
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	TrioCode [™] 128, code hopping
	Code Combinations	3.4x10 ³⁸ code combinations
	Transmitter Capacity (x4-button registers)	8
Additional Features	Courtesy Light	1 x Festoon Globe
	Safety Beam Compatibility	1 x 2-wire PE Beam
Warranty*	5 year/10,000 cycles	
Network Compatible	Ready for Smart Phone Control Kit	

POPULAR ACCESSORIES

Smart Phone Control Kit

Monitor and operate your garage door and gate on your smart phone from anywhere". Control more than one location from the one app, such as home and holiday home. Receive push notifications about the status of your garage door and gate, view past activities, set various opening modes, customise user settings and more in the Automatic Technology App.

*Subject to cellular and WiFi connection and availability.



Wireless Keypad Placed on the outside of your garage, our keypad delivers weatherproof, secure access without a remote control or keys. Perfect for school kids and active families.



Wired Safety Beams Using a 2-wire system, these safety beams help protect your family and possessions by detecting obstructions while your door is closing.

SAFETY & SECURITY FEATURES



Soft Start/Soft Stop



Intelligent Safety System



Door Profiling



TrioCode™128

POWER & MOUNTING SYSTEMS



DC Motor



Belt Drive (optional)



Low Headroom

OPERATING MODES & FEATURES



Standard Courtesy Light



Service Indicator



Auxiliary Output

See our website for our icon glossary explanations.

Proudly Distributed by:

THE BRAND TRUSTED BY GARAGE & GATE ACCESS PROFESSIONALS



