

YOUR 'GO TO' ROLLING DOOR OPENER

Our flagship rolling door opener, the EasyRoller® now features our Series 2 upgrades. Designed to deliver a slim profile, reliability, security and convenience, it is compatible with our Smart Phone Control Kit and Wireless Safety Beams.

The Series 2 EasyRoller® takes forward the impressive reputation earned by this series of openers over the past decade. This version incorporates bright LED courtesy lighting. The opener comes with TrioCode™128 Remote Controls, Soft Start/Soft Stop operation, advanced door profiling and obstruction sensing for secure and safe operation. The Service Indicator lets you know when it is time to service your door.

WHAT'S IN THE BOX:







Easy Access Transmitter to open and close the door from within the garage



Two TrioCode™128 Remote Controls

AT A GLANCE:



SECURE & RELIABLE REMOTE CONTROL

The TrioCode™128 remote control ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol (with trillions upon trillions of random codes*) for the ultimate in security.

*340,282,366,920,938,463,463,374,607,431,768,211,456 codes

POWERFUL MOTOR

This EasyRoller® 600N DC motor reliably operates doors up to 110kg².

LED COURTESY LIGHT

A Courtesy Light means your immediate surrounds can be lit to provide security and convenience, and being an LED light source you know it's going to last.

7 YEAR WARRANTY

The Series 2 EasyRoller® is backed by a 7-year/20,000 cycle warranty*, giving peace of mind.

www.automatictechnology.com.au Phone: 1300 133 944



[^]When maximum spring balanced weight is 20kg.

^{*}Please see full warranty terms and conditions on our website. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under the Australian Consumer Law.

EASY ROLLER GDO-6 GEN2

TECHNICAL SPECIFICATIONS

Power	Input Voltage	230-240V a.c. 50Hz
	Transformer Rating	100VA
	Standby Power	2.2W
	Motor Type	24V d.c. Permanent Magnet
	Motor Power	100W
	Short-term Lifting Force	600N
Door Sizes	Maximum Door Weight [^]	110kg
	Rated Door Area	16.5m²
	Typical Travel Speed	130mm/sec
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	TrioCode [™] 128, code hopping
	Code Combinations	3.4x10 ³⁸ code combinations
	Transmitter Capacity (x 4-button registers)	64
Additional Features	Courtesy Light	2 x LED
	Safety Beam Compatibility	2 x Wireless or 2-wire Safety Beams
Warranty*	7 year/20,000 cycles	
Network Compatible	Ready for Smart Phone Control Kit	

POPULAR ACCESSORIES

Smart Phone Control Kit

Monitor and operate your garage door and gate on your smart phone from anywhere". Control more than one location from the one app, such as home and holiday home. Receive push notifications about the status of your garage door and gate, view past activities, set various opening modes, customise user settings and more in the Automatic Technology App.

*Subject to cellular and WiFi connection and availability.



Battery Back Up
In the event of power failure
your door will still operate.



SmartSolar™ Ready
Using only one solar panel the sun does all the work for you.



Wireless Safety Beams Safety beams help protect your family and possessions by detecting obstructions while your door is closing.

SAFETY & SECURITY FEATURES



Soft Start/Soft Stop



Intelligent Safety System



Door Profiling



<mark>:8</mark> TrioCode™*12*8

POWER & MOUNTING SYSTEMS



DC Motor



Slim Fit

OPERATING MODES & FEATURES



Wireless Safety Beam Ready



LED Courtesy Lights



Auto Close (with Safety Beams)



Service Indicator



Ventilation Mode



Vacation Mode



Auxiliary Output

See our website for our icon glossary explanations.

Proudly Distributed by:

THE BRAND TRUSTED BY GARAGE & GATE ACCESS PROFESSIONALS



